[c2]

[c3]

[c4]

the first feet from the first first from the feet from the

CLAIMS

[c1] 1. In a controller, a method for putting an inactive net in a group communication network into a dormant mode, the method comprising:

determining whether the net has been inactive for a predetermined time period; and causing the net to enter the dormant mode if it is determined that the net has been inactive for the predetermined time period.

- 2. The method of claim 1, wherein the causing includes ordering each participating communication device in the net to release its air-traffic channel.
- The method of claim 2 further including:
 maintaining sufficient connection for each participating communication device in the net
 for sending an out-of-dormant command.
- 4. The method of claim 2, wherein each participating communication device may ignore a go-dormant order.
- [c5] 5. The method of claim 1, further including:

 causing a new communication device attempting to participate in the net to enter the dormant mode.
- [c6] 6. The method of claim 1, further including:
 informing each participating communication device in the net that the net is put in the dormant mode.
- [c7] 7. In a controller, a method for bringing a net in a group communication network out of a dormant mode, the method comprising:

receiving a floor-control request from a participating communication device in the net; and

bringing the net out of the dormant mode if the request is granted.

[c10]

[c11]

- [c8] 8. The method of claim 7, wherein the bringing the net out of the dormant mode includes sending wake-up commands to participating communication devices in the net before bringing the net out of the dormant mode.
- [c9] 9. The method of claim 8, further including:

 receiving responses to the wake-up commands from a number of participating communication devices in the net before bringing the net out of the dormant mode; and

bringing the net out of the dormant mode if the number exceeds a predetermined threshold number.

- 10. The method of claim 9, further including: un-registering communication devices that fail to respond to the wake-up requests within a predetermined time period.
 - 11. The method of claim 10, further including: re-registering a communication device that later asks to re-join the net.
- [c12] 12. The method of claim 8, further including:

 bringing the net out of the dormant mode after a predetermined time period following sending the wake-up requests.
- [c13] 13. The method of claim 7, further including:

 buffering information received from the participating communication device before bringing the net out of the dormant mode.
- [c14] 14. The method of claim 7, wherein the receiving includes receiving the floor-control request from a push-to-talk (PTT) device.
- [c15] 15. In a controller, a computer-readable medium embodying a method for putting an inactive net in a group communication network into a dormant mode, the method comprising: determining whether the net has been inactive for a predetermined time period; and causing the net to enter the dormant mode if it is determined that the net has been inactive for the predetermined time period.

16. [c16] In a controller, a computer-readable medium embodying a method for bringing a net in a group communication network out of a dormant mode, the method comprising:

receiving a floor-control request from a participating communication device in the net; and

bringing the net out of the dormant mode if the request is granted.

17. [c17] A controller for bringing a net in a group communication network out of a The state of the s dormant mode, comprising:

means for receiving a floor-control request from a communication device in the net; and means for bringing the net out of the dormant mode if the request is granted.

18. A controller for putting a net in a group communication network into a dormant mode, comprising:

means for determining whether the net has been inactive for a predetermined time period; and

means for causing the net to enter the dormant mode if it is determined that the net has been inactive for the predetermined time period.

[c19] 19. A controller for putting an inactive net in a group communication network into a dormant mode, comprising:

a receiver to receive information over the network;

a transmitter to transmit information over the network; and

a processor communicatively coupled to the receiver and the transmitter, the processor being capable of:

determining whether the net has been inactive for a predetermined time period; and causing the net to enter the dormant mode if it is determined that the net has been inactive for the predetermined time period.

[c20] 20. A controller for bringing a net in a group communication network out of a dormant mode, comprising:

a receiver to receive information over the network;

a transmitter to transmit information over the network; and

[c22]

a processor communicatively coupled to the receiver and the transmitter, the processor being capable of:

receiving a floor-control request from a participating communication device in the net; and

bringing the net out of the dormant mode if the request is granted.

[c21] 21. In a controller, a method for putting an inactive communication device in a group communication network into a dormant mode, the method comprising:

determining whether the communication device has been inactive for a predetermined time period; and

causing the communication device to enter the dormant mode if it is determined that the communication device has been inactive for the predetermined time period.

- 22. The method of claim 21, wherein the causing includes ordering the communication device to release its air-traffic channel.
- [c23] 23. The method of claim 22 further including: maintaining sufficient connection for the communication device for sending an out-of-dormant command.
- [c24] 24. The method of claim 22, wherein the communication device may ignore a godormant order.
- [c25] 25. In a controller, a method for bringing a communication device in a group communication network out of a dormant mode, the method comprising:

receiving a floor-control request; and

bringing the communication device out of the dormant mode if the request is granted.